



## MICRODYNE® MINI ANECHOIC CHAMBERS

IAC Bulletin MAC/1.01

**IAC Mini Anechoic Chambers provide a compact, low-cost anechoic test environment in which manufacturers of small devices and components can measure, accurately, the noise emissions of their products.**

- Custom-designed and manufactured to almost any size/specification
- High performance - typical cut-off frequency of 300 Hz
- Low cost (compared to 'walk-in' rooms)
- Fully assembled, ready to use
- Ideal for both product development and quality control testing
- Hundreds in use throughout the world
- Larger anechoic and semi-anechoic test rooms also available
- BS EN ISO 9001 quality registered

**IAC MINI ANECHOIC CHAMBERS ARE IDEAL FOR TESTING AND DEVELOPING A WIDE RANGE OF PRODUCTS INCLUDING:**

- Telecoms equipment, including cellphones
- Speakers and other audio/video devices
- Small household appliances
- Small motors and fans
- Computer disc drives
- Medical instruments
- Automotive components



IAC House, Moorside Road, WINCHESTER,  
Hampshire, SO23 7US, United Kingdom.  
Tel: +44 (0) 1962 873000 Fax: +44 (0) 1962 873111  
E-mail: [info@iacl.co.uk](mailto:info@iacl.co.uk) Website: [www.iacl.co.uk](http://www.iacl.co.uk)

iac  
product datasheet

# MICRODYNE® MINI ANECHOIC CHAMBERS -

## Designed And Built For You

Microdyne® mini anechoic chambers are designed and constructed by IAC to accommodate the specific products and test methods of individual customers. The size of the unit is calculated to take account of how and where it will be used. Optional features also include:

- Single or double-leaf acoustic doors
- Mesh shelves and hangers to support the test subject
- Wall penetrations for cables, wires etc - in any chosen position
- A variety of colours for foam wedges and exterior finish

### TYPICAL SPECIFICATION

Dimensions (approximate):

Outside - 1400mm x 1400mm x 2000mm  
high

Inside - 900mm x 900mm x 1500mm  
high (between wedge tips)

Construction (outer casing):

100mm thick Noishield® modular  
acoustic panels

Wedges: Fire-retardant, open cell foam

Noise Reduction:

Outside to inside 50dBA

Cut-Off Frequency: 300 Hz

Weight: Approx 800Kg

Finish (exterior):

Polyester Powder Coat (PPC)



IAC is a BS EN  
ISO 9001 quality  
registered company

### OTHER ACOUSTIC TEST ENVIRONMENTS AVAILABLE FROM IAC

IAC is one of the world's leading specialists in the design and construction of anechoic and semi-anechoic testing rooms and other types of acoustic test environments. It has built research and product development facilities for hundreds of international manufacturers, universities and government organisations, often using the unique and revolutionary metal-faced Metadyne® anechoic wedge system (shown below, left).

Please contact us for more information or view our web site: [www.iac.co.uk](http://www.iac.co.uk)



#### United Kingdom

IAC House, Moorside Road,  
WINCHESTER,  
Hampshire, SO23 7US  
Tel: +44 (0) 1962 873000  
Fax: +44 (0) 1962 873111  
E-mail: [info@iac.co.uk](mailto:info@iac.co.uk)  
Website: [www.iac.co.uk](http://www.iac.co.uk)

#### Germany

Sohlweg 17,  
D-41372 Niederkrüchten  
Tel: (02163) 99910  
Fax: (02163) 999123  
E-mail: [iac.gmbh@t-online.de](mailto:iac.gmbh@t-online.de)  
Website: [www.iac-gmbh.de](http://www.iac-gmbh.de)

#### Denmark

HM Akustik A/S,  
Jernholmen 44,  
DK-2650 Hvidovre  
Tel: +45 36 77 88 00  
Fax: +45 36 77 50 88  
E-mail: [mail@hm-akustik.dk](mailto:mail@hm-akustik.dk)  
Website: [www.hm-akustik.dk](http://www.hm-akustik.dk)

#### United States

1160 Commerce Avenue,  
Bronx,  
New York 10462-5599  
Tel: (718) 931 8000  
Fax: (718) 863 1138  
E-mail: [info@industrialacoustics.com](mailto:info@industrialacoustics.com)  
Website: [www.industrialacoustics.com](http://www.industrialacoustics.com)